

LUV-250 VIDEO TRANSMITTER

2.4 GHz

This is a World's smallest 2.4 GHz video transmitter made for special applications. This transmitter comes in 8 different channels in 2.4 GHz range. This unit can be used in the wide temperature range -40°C up to 75°C! The range is app. 5 km line-of-sight from the AIR.

The best "flying" model



FEATURES:

- 2.4 GHz Band
- 8 channels
- Smallest and lightest transmitter
- SMA antenna connector
- 7.5 V – 14.4 V battery operated
- Audio/video inputs
- Broadcast picture quality
- Very long range
- Recommended receiver VRX series

Technical Specifications	LUV-250
Operating Frequencies:	2300 MHz- 2500 MHz
Channels:	Selectable from 1-4 (4-8) internally
DC Voltage:	9 V
RF power:	250 m W
Minimum required voltage:	7.5 V
Battery power:	12 V
Video distortion:	2%
Maximum range:	5 km from the AIR
Video Format:	PAL, NTSC
Current Consumption:	150 mA / 9 V
Antenna:	Omni Dipole recommended
Antenna Connector:	SMA
Impedance:	50 ohms
Video Connector:	RCA F or open wire
Video Impedance:	75 ohms
Video level:	1 V
Audio level:	300 mV
Temperature Range:	-40 +75* C
Dimensions:	1.5" X 1.2 " X 0.4"
Weight:	18 grams
Modulation:	WFM



rf-video
.com

www.rf-video.com,

Email to: info@rf-video.com.

Copyright. © 2002-2012