

RMX-3000 AUDIO/VIDEO RECEIVER

2.4 GHz

The newest and smallest 2.4 GHz Audio/Video receiver is an amazing product. This is definitely the World's smallest analog receiver for 2.4 GHz on the market. RMX-3000 is a fully synthesized unit with 4 easy to change channels. Smallest receiver is 9 V battery operated unit. This receiver has an SMA antenna connector and switch selector.

WORLD'S SMALLEST VIDEO RECEIVER 2.4 GHz



FEATURES:

- 4 Selectable channels
- 2.4 GHz band
- SMA antenna connector
- 9 V battery operated
- RCA video/audio outputs
- Excellent picture quality
- Very sensitive
- Smallest size

Technical Specifications	RMX-3000
Operating Frequencies:	2,410 MHz; 2,433 MHz; 2,452 MHz; 2,481 MHz
Channel:	#5, 6, 7, 8
DC Voltage:	9 V- 12 V
RF power:	N/A
Minimum required voltage:	6 V
Battery power:	9 V/ 180 mA
Video distortion:	5%
Sensitivity:	-86 dBm
Video Format:	PAL, NTSC
Current Consumption:	180 mA / 9 V
Antenna:	Recommended high gain, omni directional ant.
Antenna Connector:	SMA
Impedance:	50 ohms
Video output Connector:	RCA F
Video Impedance:	75 ohms
Audio level:	300 mV
Temperature Range:	-10 +65° C
Dimensions:	2" X 1.2 " X 0.7"
Weight:	20 grams
Demodulation:	WFM



www.rf-video.com,

Email to: info@rf-video.com.

Copyright. © 2002-2012