

XLT-902, XLT-916 VIDEO TRANSMITTERS

900 MHz

This small low power video transmitter will send an excellent image from camera to the receiver 900 MHz. You can use this transmitter with any video source 1V/ 75 ohm. The range is app. 300-500 ft maximum. This unit comes with a one-year warranty.

FCC APPROVED



FEATURES:

- 900 MHz band
- 3 operating channels available
- Built-in antenna
- 9 V battery operated
- RCA video input
- Excellent picture quality
- Max. range 500 ft
- Recommended receiver DCV-900
- Perfect for mobile operations

Technical Specifications	XLT-902, XLT-916
Operating Frequencies:	902 MHz, 916 MHz, 927 MHz
Channel:	2, 3, 4
DC Voltage:	7 V – 14.4 V
RF power:	<1 mW
Battery power:	9 V
Video distortion:	2%
Maximum range:	500 ft los
Video Format:	PAL, NTSC
Current Consumption:	28 mA
Antenna:	Built-in, matched
Antenna Connector:	N/A
Video Connector:	RCA MALE
Video Impedance:	75 ohms
Video level:	1 V
Temperature Range:	-20 +75° C
Dimensions:	0.8"x 0.5"
Weight:	8 grams



www.rf-video.com,

Email to: info@rf-video.com.

Copyright. © 2002-2012